



## AGRIMAX FORCE

### Description

AGRIMAX FORCE the high-end product of BKT is a radial tire specially designed for soil tillage, haulage and harvesting applications with high-power tractors and harvesters, ensuring top performance and efficiency. Thanks to its IF technology, this tire can carry heavy loads with a lower inflating pressure compared to a standard tire reducing soil compaction. AGRIMAX FORCE features a reinforced bead and provides enhanced traction, top self-cleaning properties and fuel economy.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Harvester



Version	STANDARD
Tire Type	TL
Tyre size	IF600/70R30
LI/SS	165;D

## Dimensions IS Standard

SW (IS) (mm)	603
OD (IS) (mm)	1602
SLR (IS) (mm)	708
RC (IS) (mm)	4800
Rim Rec	DW 21 B; DW 21 A
Rim Alt	DW 20 A; DW 20 B
ECE	E11-106R-006495
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>70</b>	2200	2525	2900	3280	3650	4025	4400	4685
<b>from 65 to 40</b>	2420	2780	3190	3605	4015	4425	4840	5150
<b>30</b>	2515	2890	3315	3745	4175	4600	5030	5355
<b>20</b>	2610	3000	3445	3890	4335	4775	5225	5560
<b>10</b>	3070	3530	4050	4575	5095	5615	6145	6540
<b>Upto 30 Cyc</b>	3145	3610	4145	4685	5215	5750	6290	6695
<b>Upto 15 Cyc</b>	3750	4305	4940	5585	6220	6855	7500	7980
<b>Upto 10 Cyc</b>	4110	4725	5420	6125	6825	7520	8225	8755
<b>10 HT</b>	2515	2890	3315	3745	4175	4600	5030	5355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..