



AS 504

Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

UM

US Standard

Construction

 Bias

Machinery

Agriculture ▪ Telehandler, Industrial & Construction ▪
Telehandler



Version

STANDARD

Tire Type

TT

Tyre size

11.5/80-15.3

LI/SS

Dimensions US Standard

USA Code	94018710
SW (US) (in)	11.4
OD (US) (in)	34.1
SLR (US) (in)	15.0
RC (US) (in)	100.0
Rim Rec	9.00
ECE	E4-106R-001894

Load Capacity (US)

mph / psi	59
5 FR	6720
15 FR	5720
20 FR	5380
25 FR	4810
5 DW	4780
15 DW	4070
20 DW	3820
25 DW	3420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..