



US standard



GROWING TOGETHER

# EM 939



PRODUCT DATA SHEET



Bias

Technologies



Deep Tread



# EM 939

EM 939 has been specially designed for excavators in road construction applications. It has a deeper tread and more lugs ensuring an extended tire life-cycle. The special lug design provides excellent traction during on/off road operations. The tire shows best lateral traction as well as outstanding self-cleaning features. The unique tread compound offers cut and chip resistance whereas the strong casing provides a long service life.

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 20"	94064281	9.00 - 20	TT	16	-	STD	40.4	10.2	-	-	33	114	7.0	6.5; 7.5
	94067848	9.00 - 20	TT	18	-	STD	40.4	10.2	-	-	33	114	7.0	6.5; 7.5
	94064052	10.00 - 20	TT	18	-	STD	42.3	11.0	-	-	35	126	7.5	7.0; 8.0

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference