



AW 909

Description

AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement machinery, trailers and balers. It is ideal for modern farming both on and off the road.

UM

IS Standard

Construction

 Bias

Machinery

Agriculture ■ Baler



Version	STANDARD
Tire Type	TL
Tyre size	15.0/55-17
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	391
OD (IS) (mm)	850
SLR (IS) (mm)	377
RC (IS) (mm)	2490
Rim Rec	13.00
Rim Alt	13
ECE	E11-106R-003515

Load Capacity (IS)

km/h / bar	3.10
10 FR	3305
25 FR	2810
30 FR	2645
40 FR	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..