



AGRIMAX V-FLECTO



AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tyre is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tyres, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tyre. BKT has designed this tyre with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

IS Standard

 Radial

Agriculture ■ High-Power Tractor

STEEL BELTED SPL

TL

VF710/70R42

undefined IS Standard

720

2058

928

6233

DW 25 B

DW 23 B; DW 24 B

E11-106R-009053

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8	3.2
70	3875	4500	5130	5865	6490	7120	7850	8270	9105	9840
from 65 to 40	4255	4945	5635	6440	7130	7820	8625	9085	10005	10810
30	4345	5045	5750	6570	7275	7980	8800	9270	10210	11030
20	4430	5145	5865	6700	7420	8135	8970	9450	10410	11245
10	4685	5440	6200	7085	7845	8605	9490	9995	11010	11895
Upto 30 Cyc	4830	5615	6395	7310	8095	8875	9790	10310	11355	12270
Upto 15 Cyc	5765	6700	7635	8725	9660	10595	11685	12310	13555	14650
Upto 10 Cyc	6320	7345	8370	9565	10590	11615	12810	13490	14860	16055
10HT	4345	5045	5750	6570	7275	7980	8800	9270	10210	11030

25-02-2026