



US standard



GROWING TOGETHER

# LG RIB



PRODUCT DATA SHEET



Bias



# LG RIB

LG RIB is a lawn and garden tire suitable for mowers and small tractors. Its tread pattern has been designed for making the tire gentle on the ground to prevent turf damages making handling easier at the same time. LG RIB is available in an "aramid-belted" version for users who need strengthened puncture resistance.

### Technologies



Aramid Belted

### Performance



Comfort



Field Protection



High Puncture Resistance



Steering Control

|              | US CODE  | Tire size                  | RIM                             |                                | S.W.<br>(In.) | O.D.<br>(In.) | SLR<br>(In.) | RC<br>(In.) | TREAD<br>DEPTH<br>(32nds) | TIRE<br>WEIGHT<br>(lbs) | Version | PR | Type | LI/SS |
|--------------|----------|----------------------------|---------------------------------|--------------------------------|---------------|---------------|--------------|-------------|---------------------------|-------------------------|---------|----|------|-------|
|              |          |                            | Rec.                            | Alt.                           |               |               |              |             |                           |                         |         |    |      |       |
| <b>Ø 5"</b>  | 94074686 | <b>11 X<br/>4.00 - 5</b>   | 3.00 A                          | -                              | 4.1           | 10.7          | -            | -           | 4                         | 3                       | STD     | 4  | TL   | 39 A6 |
| <b>Ø 6"</b>  | 94013012 | <b>13 X<br/>5.00 - 6</b>   | 3.50 A                          | -                              | 5.0           | 12.8          | 5.7          | 37.1        | 3                         | 4                       | AB      | 6  | TL   | -     |
|              | 94012930 | <b>13 X<br/>5.00 - 6</b>   | 3.50 A                          | -                              | 5.0           | 12.8          | 5.7          | 37.1        | 3                         | 3                       | STD     | 4  | TL   | -     |
|              | 94013029 | <b>15 X<br/>6.00 - 6</b>   | 4.50 A                          | -                              | 6.0           | 14.4          | 6.3          | 41.7        | 4                         | 6                       | AB      | 6  | TL   | -     |
|              | 94012954 | <b>15 X<br/>6.00 - 6</b>   | 4.50 A                          | -                              | 6.0           | 14.4          | 6.3          | 41.7        | 4                         | 4                       | STD     | 4  | TL   | -     |
|              | 94012961 | <b>15 X<br/>6.00 - 6</b>   | 4.50 A                          | -                              | 6.0           | 14.4          | 6.3          | 41.7        | 4                         | 4                       | STD     | 6  | TL   | -     |
| <b>Ø 8"</b>  | 94052165 | <b>16 X<br/>6.50 - 8</b>   | 5.375 I - 55;<br>I - 70; I - 90 | -                              | 6.7           | 16.1          | 7.2          | 46.6        | 3                         | 9                       | AB      | 10 | TL   | -     |
|              | 94013036 | <b>16 X<br/>6.50 - 8</b>   | 5.375 I - 55;<br>I - 70; I - 90 | -                              | 6.7           | 16.1          | 7.2          | 46.6        | 3                         | 7                       | AB      | 6  | TL   | -     |
|              | 94012978 | <b>16 X<br/>6.50 - 8</b>   | 5.375 I - 55;<br>I - 70; I - 90 | -                              | 6.7           | 16.1          | 7.2          | 46.6        | 3                         | 6                       | STD     | 4  | TT   | -     |
|              | 94012985 | <b>16 X<br/>6.50 - 8</b>   | 5.375 I - 55;<br>I - 70; I - 90 | -                              | 6.7           | 16.1          | 7.2          | 46.6        | 3                         | 7                       | STD     | 4  | TL   | -     |
|              | 94013005 | <b>16 X<br/>6.50 - 8</b>   | 5.375 I - 55;<br>I - 70; I - 90 | -                              | 6.7           | 16.1          | 7.2          | 46.6        | 3                         | 7                       | STD     | 6  | TL   | -     |
|              | 94041701 | <b>16 X<br/>6.50 - 8</b>   | 5.375 I - 55;<br>I - 70; I - 90 | -                              | 6.7           | 16.1          | 7.2          | 46.6        | 3                         | 7                       | STD     | 8  | TL   | -     |
|              | 94030866 | <b>16 X<br/>6.50 - 8</b>   | 5.375 I - 55;<br>I - 70; I - 90 | -                              | 6.7           | 16.1          | 7.2          | 46.6        | 3                         | 8                       | STD     | 10 | TL   | -     |
| <b>Ø 10"</b> | 94026128 | <b>20 X<br/>10.00 - 10</b> | 8.00 I - 55;<br>I - 70; I - 90  | 7.00 I - 55;<br>I - 70; I - 90 | 9.3           | 19.6          | 8.7          | 56.9        | 8                         | 12                      | STD     | 4  | TL   | -     |

AB: Aramid Belted - STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference