



US standard



GROWING TOGETHER

# AT 316



PRODUCT DATA SHEET



Bias



# AT 316

 AT 316 is suitable for compact utility tractors in municipality and maintenance applications. The special tread design provides excellent traction without compromising field protection - an essential feature for this kind of application. AT 316 is also available as "aramid-belted" version to provide increased puncture resistance.

## Performance



Self-Cleaning



Traction

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 12"	94001200	24 X 12.00 - 12	10.50   - 55;   - 70;   - 90	-	12.4	24.0	10.7	69.6	15	22	STD	4	TL	-
	94001217	24 X 12.00 - 12	10.50   - 55;   - 70;   - 90	-	12.4	24.0	10.7	69.6	15	25	AB	6	TL	-

STD: Standard - AB: Aramid Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference