



US standard



GROWING TOGETHER

# RM 500



PRODUCT DATA SHEET



Radial



# RM 500

RM 500 is a steel-belted radial tire suitable for harvester implement applications. It features a strong casing and a special tread design providing high load capacity and particular cut-and-chip resistance. Thanks to its large footprint, RM 500 ensures great pressure distribution on the ground with reduced soil compaction in addition to excellent traction.

### Technologies



Steel Belted

### Performance



High Load Capacity



Stability



Traction



High Puncture Resistance

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 24"	94062430	500/70 R 24	167 A8/ 155 A8	W 16 L	W 15 L	19.8	51.6	22.5	153.8	48	248	SB
	94075522	500/85 R 24	182 A8/ 170 A8	W 16 L	W 15 L	20.5	57.5	24.5	172.5	48	324	SB
	94061570	500/85 R 24	182 A8/ 170 A8	W 16 L	W 15 L	20.5	57.5	24.5	172.5	48	317	SB
Ø 28"	94063697	500/80 R 28	176 A8/ 164 A8	W 16 L	W 15 L	19.8	58.9	25.0	171.5	48	333	SB
	94063666	600/65 R 28	168 A8/ 156 A8	W 18 L	W 20 L	23.2	58.5	25.2	170.9	64	389	SB
	94070961	600/65 R 28	177 A8/ 165 A8	W 18 L	W 20 L	23.2	58.5	25.2	170.9	64	384	SB
Ø 30"	94065097	500/85 R 30	176 A8/ 164 A8	W 16 L	W 15 L	21.1	63.4	26.5	186.8	48	367	SB

SB: Steel Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference