



## RIDEMAX FL 615



### Description

RIDEMAX FL 615 is a radial flotation tire suitable for non-driven wheels of trailers, tankers and spreaders. The steel-belted structure offers high puncture resistance along with increased durability and high load capacity. RIDEMAX FL 615 provides low rolling resistance on the road with outstanding self-cleaning properties in the fields. The rounded shoulder and wide footprint area ensure best soil protection.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Trailer

Version	STEEL BELTED
Tire Type	TL
Tyre size	VF900/65R38
LI/SS	200;D

## Dimensions US Standard

USA Code	94515349
SW (US) (in)	35.1
OD (US) (in)	83.3
SLR (US) (in)	36.6
RC (US) (in)	253.7
Rim Rec	DW 30 B
ECE	E11-106R-0011504

## Load Capacity (US)

mph / psi	15	17	23	29	35	41
40	15120	16970	20680	23460	27160	30860
30	17700	19860	24190	27450	31780	36110
25	19510	21900	26690	30270	35040	39810
20	21330	23940	29170	33080	38300	43520
15	22090	24790	30190	34250	39660	45060
10	22990	25800	31440	35660	41290	46910
5	24810	27840	33920	38470	44540	50620

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..