



US standard



GROWING TOGETHER

# TR 461



PRODUCT DATA SHEET



Bias



Performance



Cut and Chip Resistance



Durability



Road Oriented



Stability



# TR 461

TR 461 is a BKT pattern suitable for municipality and maintenance applications with tractors as well as for loading operations with telehandlers. The sidewall protection features particular resistance against cuts and bruises providing a longer life even on hard surfaces in addition to excellent stability.

	US CODE	Tire size	Type	PR	LI/SS		Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
					DW	FR								Rec.	Alt.
Ø 18"	94028344	12.5/80 - 18	TL	12	129 A8	142 A8	STD	38.9	12.0	17.1	114.3	35	100	W 9	11
	94067428	12.5/80 - 18	TL	18	138 A8	150 A8	STD	38.9	12.0	17.1	114.3	35	102	W 9	11
Ø 24"	94016747	16.9 - 24	TL	14	151 A8		STD	50.4	17.3	22.3	148.1	32	205	DW 15 L	DW 14 L
	94016761	19.5 L - 24	TL	12	151 A8		STD	51.6	19.9	23.3	153.9	36	250	DW 16 L	-
	94016778	19.5 L - 24	TL	14	154 A8		STD	51.6	19.3	22.8	151.6	36	250	DW 16 L	-
	94016785	21 L - 24	TL	14	157 A8		STD	54.5	21.3	23.9	160.3	40	301	DW 18 L	-
Ø 28"	94016754	16.9 - 28	TL	14	154 A8		STD	54.7	17.3	24.4	160.9	32	228	DW 15 L	DW 14 L
Ø 34"	94067015	620/60 B 34	TL	-	175 A8		HD	64.1	24.2	29.5	194.1	37	488	DW 20 B	-

STD: Standard - HD: Heavy Duty



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling