



RIB MASTER

Description

RIB MASTER is suitable for transport and hay harvesting operations with trailers, balers and implement machinery. This tire offers great load capacity and a long tire life-cycle.

UM

US Standard

Construction

Machinery

Agriculture ■ Baler



Version

STANDARD

Tire Type

TL

Tyre size

215/75-17.5

LI/SS

Dimensions US Standard

USA Code	94010905
SW (US) (in)	8.7
OD (US) (in)	30.5
SLR (US) (in)	14.2
RC (US) (in)	90.9
Rim Rec	6.75
ECE	E11-106R-004593

field_2

mph / psi	131
5 FR	8130
15 FR	6960
20 FR	6550
25 FR	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..