



IS standard



GROWING TOGETHER

LOADER SPECIAL



PRODUCT DATA SHEET



Bias



LOADER SPECIAL

LOADER SPECIAL (L-5) is a bias-ply tire that keeps your loaders on the move and provides top efficiency in heavy-duty rock operations. Optimum traction and exceptional cut resistance will boost productivity.

Technologies



Extra Deep Tread

Performance



Cut Resistance



Heavy Duty



Traction

Ø	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
25"	20.5 - 25	TL	L-5	20	-	STD	-	530	1570	-	-	85	17.00/2.0	-
	26.5 - 25	TL	L-5	32	-	STD	-	686	1815	833	5372	93	22.00/3.0	-
	26.5 - 25	TL	L-5	28	-	STD	-	686	1815	833	5372	93	22.00/3.0	-
	29.5 - 25	TL	L-5	28	-	STD	-	770	1930	884	5753	99	25.00/3.5	-
	29.5 - 25	TL	L-5	32	-	STD	-	770	1930	884	5753	99	25.00/3.5	-
33"	35/65 - 33	TL	L-5	42	-	STD	-	910	2105	976	6505	99	28.00/3.5	-
39"	40/65 - 39	TL	L-5	56	-	SB	-	1000	2405	-	-	108	32.00/4.0	-
45"	45/65 - 45	TL	L-5	58	-	SB	-	1185	2785	-	-	116	36.00/4.5	-

STD: Standard - SB: Steel Belted



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference