



EARTHMAX SR 44



Description

EARTHMAX SR 44 (E-4) is an All Steel radial tire suitable transport applications with tippers. The rugged E-4 tread pattern provides both excellent traction and operator comfort. EARTHMAX SR 44 (E-4) ensures also great high load capacity and extraordinary durability.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ On/Off Truck

Version STANDARD

Tire Type TT

Tyre size 12.00R20

LI/SS

Dimensions IS Standard

OD (IS) (mm)	1138
SLR (IS) (mm)	532
RC (IS) (mm)	3408
Rim Rec	8.50V
Rim Alt	9.00V
TRA Code	E4

Load Capacity (IS)

km/h / bar	7.75
50	4160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..