



AGRIMAX SPARGO

Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor



Version	STANDARD
Tire Type	TL
Tyre size	VF480/95R54
LI/SS	180;D

Dimensions IS Standard

SW (IS) (mm)	509
OD (IS) (mm)	2300
SLR (IS) (mm)	1033
RC (IS) (mm)	6956
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-0011499
TRA Code	R1

Load Capacity (IS)

km/h / bar	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.8
70	4220	4735	5255	5770	6065	6360	6545	6730	7395
from 65 to 40	4560	5120	5680	6240	6560	6880	7080	7280	8000
30	4655	5225	5795	6365	6695	7020	7225	7430	8160
20	4745	5325	5910	6490	6825	7160	7365	7575	8320
10	5020	5635	6250	6865	7220	7570	7790	8010	8800
Upto 15 Cyc.	6180	6940	7700	8460	8890	9325	9595	9865	10840
Upto 30 Cyc.	5180	5815	6450	7085	7450	7810	8040	8265	9080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..