



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 475



PRODUCT DATA SHEET



Radial

E-4

B

209

EARTHMAX SR 475

RADIAL OTR TIRES



UK EARTHMAX SR 475 is an all steel radial tire specially designed for Rigid Dump Trucks. It is ideal for hard and rocky operations especially with long hauls. The unique tread design generate lower heat in hot climate and provides excellent traction. Its strong all steel casing and belts provide great stability and resistant to snags and punctures. EARTHMAX SR 475 has been developed with squared shoulder that ensures excellent maneuverability and handling, maximizing the ground contact.

Technologies



All Steel



Strong Casing

Performance



Traction



Stability



Cut Resistance



Comfort



Hard Rocky Surface

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 33"	18.00 R 33	TL	E-4	**	191 B	CRC	265	490	1860	860	5721	50	13.00/2.5	-
	18.00 R 33	TL	E-4	***	195 B	CRC	265	490	1860	860	5721	50	13.00/2.5	-
	18.00 R 33	TL	E-4	***	195 B	STDC	292	490	1860	860	5721	50	13.00/2.5	-
Ø 35"	24.00 R 35	TL	E-4	**	209 B	CRC	355	654	2160	971	6589	59	17.00/3.5	-
	24.00 R 35	TL	E-4	**	209 B	STDC	422	654	2160	971	6589	59	17.00/3.5	-

CRC: Cut Resistance Compound - STDC: Standard Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference