



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR LOADER



PRODUCT DATA SHEET



Radial



# EARTHMAX SR LOADER

RADIAL OTR TIRES



EARTHMAX SR LOADER is an OTR tire designed for loading and dozing operations as well as for Articulated dump truck application. Its All Steel casing along with multi-layer steel belts and a unique tread compound provide exceptional resistance to snags and punctures resulting in an extended service life. EARTHMAX SR LOADER features a unique tread pattern providing top self-cleaning properties and excellent traction on several types of terrain.

## Performance



Cut and Chip Resistance



Durability



High Load Capacity



High Puncture Resistance



Self-Cleaning



Traction

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
<b>Ø 25"</b>	20.5 R 25	TL	E-3/L-3	**/*	177 B/ 186 A2	CRC	170	530	1475	649	4384	29	17.00/2.0	-
	23.5 R 25	TL	E-3/L-3	**/*	185 B/ 195 A2	CRC	200	612	1605	706	4770	31	19.50/2.5	-
	26.5 R 25	TL	E-3/L-3	**/*	193 B/ 202 A2	CRC	230	681	1735	763	5179	33	22.00/3.0	-
	29.5 R 25	TL	E-3/L-3	**/*	200 B/ 208 A2	CRC	270	768	1859	818	5549	37	25.00/3.5	-

CRC: Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference