



IS standard



GROWING TOGETHER

# TR 387 IND



PRODUCT DATA SHEET



Bias



# TR 387 IND

TR 387 IND is an industrial tire suitable for industrial trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

### Technologies



Reinforced Bead

### Performance



Cut and Chip Resistance



Durability



Heavy Duty



High Load Capacity

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 30"	620/75 - 30 (23.1 - 30)	TL	16	161 A6	DB	605	1675	770	4909	DW 20 A ; DW 20 B	-
	620/75 - 30 (23.1 - 30)	TL	18	164 A6	DB HD	605	1675	-	-	DW 20 A ; DW 20 B	-
Ø 32"	24.5 - 32	TL	16	164 A6	DB HD	625	1755	790	5226	DH 21	DH 21 B ; DH 21 H ; DH 21 HB

DB: Dual Bead - DB HD: Dual Bead Heavy Duty



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference