



US standard



GROWING TOGETHER

# AW 909



PRODUCT DATA SHEET



Bias



A8



143

# AW 909



AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement machinery, trailers and balers. It is ideal for modern farming both on and off the road.

## Performance



Handling and Comfort

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 12"	94044870	10.0/75 - 12	9.00	7.0	10.4	28.0	12.3	81.9	9	29	STD	8	TL	-	116 A8
	94010493	10.0/80 - 12	9.00	7.0	10.4	28.0	12.3	81.9	9	29	STD	8	TL	-	116 A8
	94010547	10.0/80 - 12	9.00	7.0	10.4	28.0	12.3	81.9	9	29	STD	10	TL	-	121 A8
Ø 15.3"	94010394	10.0/75 - 15.3	9.00	-	10.8	29.9	13.5	87.7	11	31	STD	10	TL	-	123 A8
	94010424	10.0/75 - 15.3	9.00	-	10.8	29.9	13.5	87.7	11	32	STD	12	TL	-	126 A8
	94010448	10.0/75 - 15.3	9.00	-	10.8	29.9	13.5	87.7	11	32	STD	14	TL	-	130 A8
	94010462	10.0/75 - 15.3	9.00	-	10.8	29.9	13.5	87.7	11	39	STD	18	TL	-	135 A8
	94010677	11.5/80 - 15.3	9.00	-	11.8	33.2	14.6	97.4	11	47	STD	16	TL	-	141 A8
	94010707	11.5/80 - 15.3	9.00	-	11.8	33.2	14.6	97.4	11	48	STD	18	TL	-	143 A8
	94010585	11.5/80 - 15.3	9.00	-	11.8	33.2	14.6	97.4	11	42	STD	10	TL	-	131 A8
	94010615	11.5/80 - 15.3	9.00	-	11.8	33.2	14.6	97.4	11	43	STD	12	TL	-	135 A8
	94010646	11.5/80 - 15.3	9.00	-	11.8	33.2	14.6	97.4	11	42	STD	14	TL	-	139 A8
	94010660	11.5/80 - 15.3	9.00	-	11.8	33.2	14.6	97.4	11	45	STD	16	TT	-	141 A8
	94010721	12.5/80 - 15.3	9.00	-	12.3	35.0	15.2	102.1	11	55	STD	14	TL	-	142 A8

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling



Bias



Performance



Handling and Comfort



	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 17"	94010752	15.0/55 - 17	13.00	13	15.4	33.5	14.8	98.0	12	55	STD	10	TL	-	134 A8
	94010783	15.0/55 - 17	13.00	13	15.4	33.5	14.8	98.0	12	57	STD	12	TL	-	138 A8
	94010813	15.0/55 - 17	13.00	13	15.4	33.5	14.8	98.0	12	57	STD	14	TL	-	141 A8

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling