



AGRIMAX V-FLECTO



AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tyre is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tyres, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tyre. BKT has designed this tyre with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

US Standard

 Radial

Agriculture ■

STANDARD

TL

VF710/55R34

170;D

undefined US Standard

94513376

27.9

65.3

28.6

193.3

DW 25 B

DW 27 B

E11-106R-0010831

R1W

mph / psi	9	12	15	17	20	23	29
45	5900	6860	7940	8910	9870	10820	12040
from 40 to 25	6480	7540	8730	9790	10850	11900	13230
20	6600	7680	8900	9980	11060	12140	13490
12	6730	7840	9070	10170	11280	12380	13760
5	7120	8290	9600	10760	11930	13090	14550
*Upto 5 Cyc with front loader	9070	10550	12210	13700	15180	16670	18520
5 HT	6600	7680	8900	9980	11060	12140	13490

25-02-2026