



IS standard



GROWING TOGETHER

LIFTMAX LM 63



PRODUCT DATA SHEET



Radial



LIFTMAX LM 63

LIFTMAX LM 63 has been specially developed for industrial and logistics operations. The *All-Steel* radial tyre features a strong casing reinforced by multilayer steel belts that reduce vibration while providing enhanced stability and comfort. LIFTMAX LM 63 features a 3-rib tread design that ensures low rolling resistance as well as good wet grip and uniform tread wear, delivering improved handling performance. In addition, the deep tread extends the tyre's service life.

Technologies



All Steel

Performance



Stability



Comfort

	Tyre size	Type	STAR RATING	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 8"	180/70 R 8 (18 X 7 R 8)	TL	-	125 A5	STD	170	460	-	-	4.33 R	-
	180/70 R 8 IMP (18 X 7 R 8)	TL	-	120 A8	STD	170	460	-	-	4.33 R	-
Ø 9"	6.00 R 9	TL	-	121 A5	STD	160	542	-	-	4.00 E	-
Ø 10"	6.50 R 10	TL	-	128 A5	STD	176	592	-	-	5.00 F	5.50 F
Ø 12"	7.00 R 12	TL	-	136 A5	STD	195	675	-	-	5.00 S	-
Ø 15"	7.00 R 15	TL	-	143 A5	STD	198	738	-	-	5.50	5.00
	8.25 R 15	TL	-	153 A5	STD	240	844	-	-	6.5	7.0
Ø 20"	12.00 R 20	TL	-	176 A5	STD	325	1140	-	-	8.5	8.0
	NEWSIZE										

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference