



AGRIMAX SPARGO SB



Description

AGRIMAX SPARGO SB is a special row crop tire that is particularly suitable for tractors and sprayers in open-field spraying and row crop applications, or for specialized tractors in orchards and vineyards. Thanks to its advanced VF-technology (Very Increased Flexion), the tire is able to carry 40% heavier load compared to a standard tire of the same size at the same inflation pressure. The wide footprint ensures uniform weight distribution as well as low soil compaction in the fields.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version	STEEL BELTED
Tire Type	TL
Tyre size	VF270/95R36
LI/SS	150;D

Dimensions US Standard

USA Code	94511594
SW (US) (in)	11.0
OD (US) (in)	56.7
SLR (US) (in)	26.1
RC (US) (in)	173.1
Rim Rec	W9
ECE	E11-106R-0010612

Load Capacity (US)

mph / psi	14	17	20	23	29	35	41	46	52	58
45	3170	3580	3970	4310	4790	5050	5530	5990	6400	6730
from 40 to 25	3480	3930	4370	4730	5250	5550	6070	6590	7030	7390
20	3550	4010	4460	4830	5360	5660	6190	6720	7170	7540
12	3620	4080	4550	4930	5460	5770	6310	6850	7310	7690
5	3830	4310	4800	5210	5780	6100	6670	7240	7730	8130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..