



## COMMANDER 3 RIB



### Description

COMMANDER 3 RIB is a 3-rib pattern front tire designed for soil tillage and haulage operations. It provides excellent durability and load capacity thanks to the optimized weight distribution on center and shoulder ribs. The strong casing along with the cut-and-chip resistant compound ensure outstanding puncture resistance.

### UM

US Standard

### Construction

⊠ Bias

### Machinery

Agriculture ■ 2WD Tractor

Version	STANDARD
Tire Type	TT
Tyre size	6.00-16
LI/SS	91;A8

## Dimensions US Standard

USA Code	94046911
SW (US) (in)	6.9
OD (US) (in)	29.1
Rim Rec	4.50 E
Rim Alt	4.00 E; 5.00 F
ECE	E11-106R-004415
TRA Code	F2

## Load Capacity (US)

mph / psi	68
25	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..