



US standard



GROWING TOGETHER

FL 634 PERFORMA



PRODUCT DATA SHEET



Radial



164



FL 634 PERFORMA

The new FL 634 PERFORMA is an All Steel radial tire that meets the growing demand for logistics in agriculture. Specifically designed for vehicles such as agro trucks and tank trucks, this tire embodies great efficiency and versatility making it suitable for transport operations from the harvest field to the processing or any other farm area. Engineered for high-speed performance, it ensures excellent roadability on asphalt along with smooth and rapid transportation, an essential need in modern agriculture. The innovative open shoulder and tread design significantly enhance tire traction both on the road and in the fields providing outstanding self-cleaning properties. The tread compound, the specific construction features, and a strong steel body ply with four steel belts make FL 634 PERFORMA synonym for robustness and resistance to any kind of damage ensuring a long service life. In addition, the bead has been reinforced with a steel chafer that ensures high clamping stability in any operation mode.

Technologies



All Steel



High Speed



Directional Tread Pattern

Performance



Durability



High Load Capacity



Multi-Purpose Tires



Self-Cleaning



Traction

	US CODE	Tire size	RIM		O.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	Type	LI/SS
			Rec.	Alt.									
Ø 22.5"	94073696	600/50 R 22.5	AG 20.00	-	24.2	46.1	21.1	140.4	36	354	STD	TL	164 J

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference