



## EARTHMAX SR 44



### Description

EARTHMAX SR 44 (E-4) is an All Steel radial tire suitable transport applications with tippers. The rugged E-4 tread pattern provides both excellent traction and operator comfort. EARTHMAX SR 44 (E-4) ensures also great high load capacity and extraordinary durability.

### UM

US Standard

### Construction

 Radial

### Machinery

OTR ■ On/Off Truck

Version	STANDARD
Tire Type	TL
Tyre size	325/95R24
LI/SS	158;B

## Dimensions US Standard

USA Code	94054282
OD (US) (in)	49.2
SLR (US) (in)	22.6
RC (US) (in)	149.2
Rim Rec	8.50V
Rim Alt	9.00V
TRA Code	E4

## Load Capacity (US)

mph / psi	65	69	73	76	80	83	87	91	94	98	102
30	6800	6950	7400	7600	7850	8050	8250	8550	8800	9100	9350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..