



US standard



GROWING TOGETHER

AT 171



PRODUCT DATA SHEET



Bias



Performance



AT 171

AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 14"	94056866	28 X 9 - 14	W 7	W 6	8.1	28.1	-	-	56	37	STD	6	TL	77 A8/ 53 F
	94056873	30 X 9 - 14	W 7	W 6	8.3	29.7	-	-	56	41	STD	6	TL	77 A8/ 53 F
Ø 16"	94056842	31 X 9 - 16	W 7	W 6	8.3	30.9	-	-	56	43	STD	6	TL	80 A8/ 56 F
Ø 18"	94056835	33 X 8 - 18	W 6	W 5.5	7.9	33.3	15.4	99.4	49	45	STD	6	TL	83 A8/ 59 F
	94055166	35 X 10 - 18	W 8	-	9.5	35.4	16.4	104.2	56	62	STD	8	TL	90 A8/ 66 F
	94053780	35 X 10 - 18	W 8	-	9.5	35.4	16.4	104.2	56	61	STD	8	TT	90 A8/ 66 F
Ø 20"	94056880	33 X 9 - 20	W 7	W 6	8.1	33.0	15.2	103.0	56	44	STD	6	TL	85 A8/ 61 F
	94055173	35 X 9 - 20	W 7	W 6	7.9	35.2	16.5	105.1	56	49	STD	6	TL	85 A8/ 61 F
	94054329	35 X 9 - 20	W 7	W 6	7.9	35.2	16.5	105.1	56	48	STD	6	TT	85 A8/ 61 F
	94055180	38 X 10 - 20	W 8	W 7	9.3	37.4	17.4	111.6	56	65	STD	6	TL	93 A8/ 69 F
	94054176	38 X 10 - 20	W 8	W 7	9.3	37.4	17.4	111.6	56	64	STD	6	TT	93 A8/ 69 F
Ø 22"	94061587	35 X 9 - 22	W 7	W 6	8.3	35.0	-	-	56	46	STD	6	TL	88 A8/ 64 F
	94055203	37 X 9 - 22	W 7	W 6	8.1	37.2	17.5	109.4	56	54	STD	8	TL	88 A8/ 64 F
	94054343	37 X 9 - 22	W 7	W 6	8.1	37.2	17.5	109.4	56	53	STD	8	TT	88 A8/ 64 F
	94055197	40 X 10 - 22	W 8	W 7	9.3	39.6	18.5	116.3	56	70	STD	8	TL	95 A8/ 71 F
	94054183	40 X 10 - 22	W 8	W 7	9.3	39.6	18.5	116.3	56	69	STD	8	TT	95 A8/ 71 F
Ø 24"	94056859	40 X 9 - 24	W 7	W 6	8.3	39.2	18.2	122.5	56	60	STD	8	TL	90 A8/ 66 F

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference