



AT 111

Description

AT 111 is suitable for all-terrain sport racing with ATVs. An "HD" version with a deep tread is available for users who need improved durability and traction.

UM

IS Standard

Construction

 Bias

Machinery

Agriculture ■ ATV



Version

STANDARD

Tire Type

TL

Tyre size

AT20x11-8

LI/SS

Dimensions IS Standard

SW (IS) (mm)	282
OD (IS) (mm)	508
Rim Rec	9.0 AT
Rim Alt	8.5 AT

Load Capacity (IS)

km/h / bar	0.45
80	155

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..