



IS standard



GROWING TOGETHER

POWER TRAX HD (SS)



PRODUCT DATA SHEET



Bias



POWER TRAX HD (SS)

POWER TRAX HD premium tire is specially designed for equipment in port and underground mining applications. Its deep tread, the extra thick sidewall and the tough casing provide exceptional durability minimizing the risk of punctures and accidental damages. The tire features excellent cut and chip resistance, which is particularly suitable for rough and hard surfaces. The specially designed rim guard ensures protection against flats and wheel damage in the rim flange area.

Technologies



Strong Casing



Extra Deep Tread

Performance



Cut and Chip Resistance



Durability



High Puncture Resistance

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 16.5"	10 - 16.5	TL	10	-	STD	268	790	361	2331	8.25	-
	10 - 16.5	TL	10	120 A8	IMP	268	790	361	2331	8.25	-
	12 - 16.5	TL	10	-	STD	324	865	391	2552	9.75	-
	12 - 16.5	TL	12	-	STD	324	865	391	2552	9.75	-
	12 - 16.5	TL	14	-	STD	324	865	391	2552	9.75	-

STD: Standard - IMP: Implement



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference