



IS standard



GROWING TOGETHER

IT 400



PRODUCT DATA SHEET



Bias



143

Technologies



High Speed

Performance



Fuel Economy



Road Oriented



IT 400

IT 400 is a road-oriented rib-pattern tire for low platforms in transport applications. The tire is suitable for high-speed applications and provides significant fuel savings.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 15"	7.50 - 15	TT	16	125/121 J	STD	210	795	356	2361	6.0	5.50 F ; 6.50
	8.25 - 15	TL	14	129/125 J	STD	239	846	377	2513	6.50	6.0 ; 7.0
	8.25 - 15	TT	14	129/125 J	STD	239	846	377	2513	6.50	6.0 ; 7.0
	8.25 - 15	TT	16	131/126 J	STD	239	846	377	2513	6.50	6.0 ; 7.0
	10.00 - 15	TT	14	137/133 J	STD	274	925	408	2747	7.5	7.0 ; 8.0
	10.00 - 15	TT	16	141/136 J	STD	274	925	408	2747	7.5	7.0 ; 8.0
	10.00 - 15	TT	18	143/138 J	STD	274	925	408	2747	7.5	7.0 ; 8.0

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference