



## CON STAR

### Description

CON STAR is particularly suitable for compact loaders and telehandlers in agroindustrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

### UM

US Standard

### Construction

⊠ Bias

### Machinery

Agriculture ▪ Compact Loader, Industrial & Construction ▪ Compact Loader



Version	INDUSTRIAL
Tire Type	TL
Tyre size	400/80-24
LI/SS	162;A8

## Dimensions US Standard

USA Code	94040599
SW (US) (in)	15.9
OD (US) (in)	49.2
SLR (US) (in)	22.4
RC (US) (in)	148.9
Rim Rec	DW 13
Rim Alt	DW 12; DW 13 L; DW 14 L
ECE	E11-106R-003026

## Load Capacity (US)

mph / psi	73
25	10500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..