



IS standard



GROWING TOGETHER

# MAGLIFT EXCAVATOR



PRODUCT DATA SHEET



Solid



# MAGLIFT EXCAVATOR

MAGLIFT EXCAVATOR has been specifically designed for wheeled excavators in digging, loading and road construction operations. The tire is made of a special tread compound, which ensures excellent cut and chip resistance and an extended tire life-cycle. The aggressive tread design provides a high level of handling comfort combined with excellent lateral traction even under heavy-duty service conditions in addition to top self-cleaning properties. Its reinforced bead structure ensures best grip and eliminates any slippage risk during operations, whilst the special bead shape simplifies mounting operations on the rim. MAGLIFT EXCAVATOR is a puncture-and-maintenance-free tire operators can rely on.

## Technologies



Special Compound



Reinforced Bead

## Performance



Cut and Chip Resistance



Durability



Handling and Comfort



Traction



Self-Cleaning

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 20"	10.00 - 20	-	-	-	STD	240	1010	-	-	7.00 - 20	-
	10.00 - 20	-	-	-	STD	240	1010	-	-	7.50 - 20	-
	10.00 - 20	-	-	-	STD	246	1010	-	-	8.00 - 20	-
	12.00 - 20	-	-	-	STD	255	1100	-	-	8.00 - 20	-
	12.00 - 20	-	-	-	STD	265	1100	-	-	8.50 - 20	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference