



## EARTHMAX SR 45 M



### Description

EARTHMAX SR 45 M is an All Steel radial tire specially designed for rigid haul trucks. EARTHMAX SR 45 M provides optimum traction and is ideal for operation in long hauls.

### UM

US Standard

### Construction

 Radial

### Machinery

OTR ■ Rigid Dump Truck

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Tire Type | TL                     |
| Tyre size | 18.00R33               |
| LI/SS     | 191;B                  |

## Dimensions US Standard

|               |           |
|---------------|-----------|
| USA Code      | 94076543  |
| OD (US) (in)  | 73.6      |
| SLR (US) (in) | 33.7      |
| RC (US) (in)  | 220.8     |
| Rim Rec       | 13.00/2.5 |
| TRA Code      | E4        |

## Load Capacity (US)

| mph / psi | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 18700 | 19300 | 19800 | 20400 | 21500 | 22000 | 22700 | 23400 | 24000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..