



IS standard



GROWING TOGETHER

# LIFTMAX LM 81



PRODUCT DATA SHEET



Radial



# LIFTMAX LM 81

LIFTMAX LM 81 has been specifically designed and engineered for heavy forklift. Its aggressive and robust tread pattern together with the unique Antistatic tread compound ensures excellent wear properties and a long service life. The strong All Steel casing and the reinforced sidewall provide maximum stability and handling during lift mode, together with superior traction. In addition, its radial casing absorbs surfaces irregularities to provide better riding comfort and increase operator's confidence. LIFTMAX LM 81 is Antistatic compliant, and all its sizes are capable of dissipating static charge from the vehicle.

## Technologies



Special Antistatic Compound



All Steel

## Performance



Stability



Durability



Handling and Comfort



Traction

	Tire size	Type	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
									Rec.	Alt.
Ø 8"	5.00 R 8	TL	111 A5	STD	138	471	-	-	3.00 D	3.25 I; 3.75 I
	150/75 R 8	TL	113 A5	STD	150	430	-	-	4.33 R	-
	150/75 R 8 IMP	TL	109 A8	STD	150	430	-	-	4.33 R	-
	180/70 R 8	TL	125 A5	STD	170	453	-	-	4.33 R	-
	180/70 R 8 IMP (18 x 7 R 8)	TL	120 A8	STD	170	453	-	-	4.33 R	-
Ø 9"	6.00 R 9	TL	121 A5	STD	160	540	-	-	4.00 E	-
	200/75 R 9	TL	134 A5	STD	202	530	-	-	6.00 E	-
Ø 10"	6.50 R 10	TL	128 A5	STD	178	590	-	-	5.00 F	5.50 F
	225/75 R 10	TL	142 A5	STD	220	595	-	-	6.50 F	-
Ø 12"	7.00 R 12	TL	136 A5	STD	195	675	-	-	5.00 S	-
	250/75 R 12	TL	152 A5	STD	260	680	-	-	8.00	-
Ø 15"	7.00 R 15	TL	143 A5	STD	199	745	-	-	5.50	5.00
	7.50 R 15	TL	146 A5	STD	212	778	-	-	6.00	6.50
	8.25 R 15	TL	153 A5	STD	234	836	-	-	6.50	7.00

STD: Standard

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



A8



200

Technologies



Special Antistatic Compound



All Steel

Performance



Stability



Durability



Handling and Comfort



Traction



	Tire size	Type	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
									Rec.	Alt.
Ø 15"	225/75 R 15 (28 X 9 R 15)	TL	149A5	STD	226	712	-	-	7.00	-
	250/70 R 15	TL	153A5	STD	230	735	-	-	7.00	7.50
	315/70 R 15	TL	165A5	STD	305	834	-	-	8.00	-
	355/65 R 15	TL	170A5	STD	350	840	-	-	10.15	-
Ø 20"	9.00 R 20	TL	160A5	STD	255	1028	-	-	7.00	7.50
	10.00 R 20	TL	166A5	STD	275	1066	-	-	7.50	8.00
	11.00 R 20	TL	170A5	STD	288	1092	-	-	8.00	8.50
	12.00 R 20	TL	176A5	STD	314	1134	-	-	8.50	8.00
	12.00 R 20	TL	176A5	IND	314	1134	-	-	8.50	8.00
Ø 24"	12.00 R 24	TT	178A5	STD	310	1235	-	-	8.50	9.00
	12.00 R 24	TL	178A5	STD	310	1235	-	-	8.50	9.00
	14.00 R 24	TL	193A5	STD	388	1415	-	-	10.00 W	10.00 ; 10.00 WA
	14.00 R 24	TL	193A5	IND	388	1415	-	-	10.00 W	10.00 ; 10.00 WA
Ø 25"	16.00 R 25	TL	200A5	STD	440	1530	-	-	11.25/2.00	13.00/2.00

STD: Standard - IND: Industrial

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference