



EARTHMAX SR 22



Description

EARTHMAX SR 22 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders operating in extreme winter conditions on ice or snow. Operators will appreciate both excellent traction and stability provided by the large and non-directional tread design.

UM

US Standard

Construction

 Radial

Machinery

Industrial & Construction ■ Grader,OTR ■ Loader

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	20.5R25
LI/SS	177;B

Dimensions US Standard

USA Code	94052431
OD (US) (in)	58.7
SLR (US) (in)	25.2
RC (US) (in)	169.9
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
TRA Code	E2/L2

Load Capacity (US)

mph / psi	58	62	65	69	73	76	80	83	87	91
30	12800	13600	14300	14800	15200	16100	-	-	-	-
5	-	-	-	-	-	21500	22000	22700	24000	24700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..