



AGRIMAX RI 818



Description

AGRIMAX RI 818 is a radial tire, that has been specifically developed for pivot irrigation applications. The radial construction offers a specially designed tread pattern that provides excellent traction in wet and muddy conditions in addition to outstanding self-cleaning properties. The AGRIMAX RI 818 radial delivers a larger footprint for improved flotation compared to standard bias tires. When properly inflated, farmers will experience less soil compaction, shallower tire tracks/ruts.

UM

US Standard

Construction

 Radial

Machinery

Agriculture • Pivot Irrigator

Version	STANDARD
Tire Type	TL
Tyre size	320/85R38
LI/SS	154;

Dimensions US Standard

USA Code	94065585
SW (US) (in)	12.6
OD (US) (in)	59.4
SLR (US) (in)	27.2
RC (US) (in)	179.7
Rim Rec	W 10
Rim Alt	W 9; W 11

Load Capacity (US)

mph / psi	23
CREEP	8250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..