



EM 937 E3 (L)



Description

EM 937 (E-3/L-3) has been specially designed for loaders and backhoe loaders in dig and load applications, depending on the size. It features excellent durability and provides cut and chip resistance.

UM

IS Standard

Construction

⊠ Bias

Machinery

Industrial & Construction ■ Backhoe Loader

Version	STANDARD
Tire Type	TT
Tyre size	14.00-24
LI/SS	

Dimensions IS Standard

OD (IS) (mm)	1368
SLR (IS) (mm)	628
RC (IS) (mm)	4050
Rim Rec	10.00 W
TRA Code	E3/L3

Load Capacity (IS)

km/h / bar	07:25:00	10:00:00																	
50	6030	-																	
10	-	10470																	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..