



LG 306

Description

LG 306 is a lawn and garden tyre suitable for mowers. In some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tyre gentle on the ground, easing handling at the same time. LG 306 is available in an "aramidbelted" version for users who need strengthened puncture resistance.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■



Version	STANDARD
Tyre Type	TL
Tyre size	20x8.00-10
LI/SS	

Dimensions IS Standard

SW (mm)	205
OD (mm)	500
SLR (mm)	223
RC (mm)	1450
Rim Rec	6.00 I - 55; I - 70; I - 90
Rim Alt	6 JA
ECE	E11-106R-003454

Load Capacity (IS)

km/h / bar	1.70
15	412

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..