



STEER GRIP

Description

STEER GRIP is the perfect steering-axle fitment for on/off trucks. The wide central rib with straight lugs makes the tyre suitable for free rolling applications and provides enhanced grip for excellent performance on both wet and dry conditions off the road. The special tread compound has been designed for combining best wear resistance with cut- and-chip resistance whereas the strong casing ensures an extended tyre life-cycle.

UM

US Standard

Construction

⌘ Bias

Machinery

OTR ■ On/Off Truck



Version

STANDARD

Tyre Type

TT

Tyre size

11.00-20

LI/SS

Dimensions US Standard

USA Code	94052103
OD (in)	44.1
SLR (in)	20.7
RC (in)	133.7
Rim Rec	8.0
Rim Alt	7.5

Load Capacity (US)

mph / psi	110
55 LS/LD	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..