



## LIFTMAX LM 63

### Description

LIFTMAX LM 63 has been specially developed for industrial and logistics operations. The All-Steel radial tire features a strong casing reinforced by multilayer steel belts that reduce vibration while providing enhanced stability and comfort. LIFTMAX LM 63 features a 3-rib tread design that ensures low rolling resistance as well as good wet grip and uniform tread wear, delivering improved handling performance. In addition, the deep tread extends the tire's service life.

### UM

US Standard

### Construction

 Radial

### Machinery

Industrial & Construction ■ Tow Tractor



#### Version

STANDARD

#### Tire Type

TL

#### Tyre size

6.00R9

#### LI/SS

121;A5

# Dimensions US Standard

|              |          |
|--------------|----------|
| USA Code     | 94063901 |
| OD (US) (in) | 21.3     |
| Rim Rec      | 4.00E    |

## Load Capacity (US)

|           |      |
|-----------|------|
| mph / psi | 145  |
| 15        | 3200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..