

## AW 715

### Description

AW 715 is a high-performance radial tire designed for maximum performance. The steel-belted construction provides stability, as well as resistance to punctures. The contact patch combined with a rounded tread pattern reduces soil compaction in grassland and delivers superior traction on varied terrain. It is ideal for demanding agricultural operations, such as carcass supporting heavy loads at speed. This tire also stands out for smooth road performance, which further improves flotation.



### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Implements

Version	STEEL BELTED
Tire Type	TL
Tyre size	500/50R17undefined
LI/SS	149;D

## Dimensions IS Standard

SW (IS) (mm)	503
OD (IS) (mm)	940
SLR (IS) (mm)	433
RC (IS) (mm)	2890
Rim Rec	16.00
ECE	E11-106R-0011505

## Load Capacity (IS)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
65	1075	1205	1465	1660	1920	2180	2405	2635	2895	3250
50	1305	1460	1775	2010	2325	2640	2915	3190	3505	3935
40	1465	1640	1990	2255	2610	2965	3275	3585	3935	4420
25	1695	1900	2315	2620	3030	3445	3800	4160	4575	5135
10	1935	2165	2635	2985	3455	3920	4330	4740	5210	5850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L

Printed on 21-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time v  
Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected  
reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna  
industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make u  
contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Ba