



SM 55 IND-5S

Description

SM 55 IND-5S has been specially designed for reach stackers and container handlers. Its special abrasion-resistant tread compound provides an extended tire life on asphalt or concrete surfaces and offers excellent stability to vehicles in lift mode.

UM

IS Standard

Construction

◆ Bias

Machinery

Industrial & Construction ■ Container Handler



Version	GCRC
Tire Type	TL
Tyre size	18.00-25
LI/SS	

Dimensions IS Standard

OD (IS) (mm)	1665
SLR (IS) (mm)	765
RC (IS) (mm)	5118
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND5

Load Capacity (IS)

km/h / bar	10.00
10	22950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..