



## EARTHMAX SR 51



### Description

EARTHMAX SR 51 (L-5) is an All Steel radial tire specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction. The extra deep tread ensures also great stability and an extended tire life.

### UM

US Standard

### Construction

 Radial

### Machinery

OTR ■ Dozer

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	29.5R29
LI/SS	211;A2

## Dimensions US Standard

USA Code	94051113
OD (US) (in)	78.3
SLR (US) (in)	33.1
RC (US) (in)	231.2
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5; 26.00/3.5
TRA Code	L5

## Load Capacity (US)

mph / psi	58	62	65	69	73
5	36400	37500	39700	40800	43000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..