



FS 216

Description

FS 216 has a robust log design with optimum angle and wider width to enhance traction performance for loggers and skidders. It provides excellent cut and chip resistance under the most critical operating conditions and ensures maximum protection against possible damages at any time.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■



Version	STEEL BELTED
Tyre Type	TT
Tyre size	23.1-26
LI/SS	

Dimensions IS Standard

SW (mm)	587
OD (mm)	1615
SLR (mm)	726
RC (mm)	4780
Rim Rec	DW 20 A; DW 20 B
ECE	E11-106R-004635
TRA Code	LS2

Load Capacity (IS)

km/h / bar	3.20	3.00
10	6700	-
30	-	5150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..