



## AIROMAX AM 543



### Description

AIROMAX AM 543 is the ideal tire for construction applications with cranes. It shows outstanding traction and high stability. As crane tires are subject to particular stress and extreme usage conditions, AIROMAX AM 543 has been designed for providing excellent heat resistance. Besides, it is suitable for all operations requiring a high level of handling.

### UM

IS Standard

### Construction

 Radial

### Machinery

Industrial & Construction ■ Mobile Crane

Version	STANDARD
Tire Type	TL
Tyre size	385/95R25
LI/SS	170;E

## Dimensions IS Standard

OD (IS) (mm)	1355
SLR (IS) (mm)	627
RC (IS) (mm)	4156
Rim Rec	10.00/1.5

## Load Capacity (IS)

km/h / bar	9.00
70	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..