



IS standard



GROWING TOGETHER

MAGLIFT PREMIUM



PRODUCT DATA SHEET



Solid



MAGLIFT PREMIUM

MAGLIFT PREMIUM is a solid tire specially designed for heavy forklift operations in port, mining or scrap yard applications. The extra deep tread (25% more compared to the standard version) with its aggressive and robust pattern provides outstanding front and lateral traction in addition to excellent steering control. The unique tread compound ensures high cut and chip resistance resulting in an extended tire life-cycle. Additional features are low rolling resistance and a smooth run.

Technologies



Extra Deep Tread

Performance



Comfort



Cut and Chip Resistance



Durability



High Load Capacity

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 9"	6.00 - 9	-	-	-	STD	137	536	-	-	4.00 E - 9	-
	6.00 - 9	-	-	-	LIP	137	536	-	-	4.00 E - 9	-
	6.00 - 9	-	-	-	LIP-NM	137	536	-	-	4.00 E - 9	-
	6.00 - 9	-	-	-	STD-NM	137	536	-	-	4.00 E - 9	-
Ø 10"	6.50 - 10	-	-	-	STD	150	582	-	-	5.00 F - 10	-
	6.50 - 10	-	-	-	LIP	150	582	-	-	5.00 F - 10	-
Ø 12"	7.00 - 12	-	-	-	STD	163	664	-	-	5.00 S - 12	-
	7.00 - 12	-	-	-	LIP	163	664	-	-	5.00 S - 12	-

STD: Standard - LIP: LIP Version - LIP-NM: LIP Non Marking - STD-NM: Standard Non Marking



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference