



IS standard



GROWING TOGETHER

AT 625



PRODUCT DATA SHEET



Bias



Technologies



Extra Deep Tread

Performance



Cut and Chip Resistance



High Puncture Resistance



Stability



Traction



AT 625

The AT 625 tire is designed for backhoe loaders and compact loaders, excelling in all farming, digging, and loading operations. It's also an ideal choice for sugarcane harvesting, offering the reliability needed to keep you productive throughout the season. With its extra deep tread, the AT 625 ensures increased puncture resistance and durability, allowing you to tackle tough conditions with confidence. This tire delivers outstanding traction and stability, combined with enhanced cut and chip resistance, making it a durable and dependable partner for your agricultural tasks.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 24"	14.9 - 24	TL	12	145 A8	STD	400	1265	575	3800	DW 13	DW 11 ; DW 12 ; DW 13 L
	14.9 - 24	TT	12	145 A8	STD	400	1265	575	3800	DW 13	DW 11 ; DW 12 ; DW 13 L
Ø 28"	16.9 - 28	TL	12	152 A8	IND	450	1415	645	4254	DW 15 L	DW 14 L
	16.9 - 28	TT	12	152 A8	IND	450	1415	645	4254	DW 15 L	DW 14 L
	16.9 - 28	TT	12	152 A8	SPL	450	1415	645	4254	DW 15 L	DW 14 L

STD: Standard - IND: Industrial - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference