



## EM 936 SUPER



### Description

EM 936 SUPER has been specifically designed for excavators and telehandlers in digging and loading operations as well as transport applications. With increased tread width by 8-10%, EM 936 SUPER offers outstanding stability and enhanced riding comfort. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions.

### UM

IS Standard

### Construction

 Bias

### Machinery

Industrial & Construction ■ Excavator

Version	STANDARD
Tire Type	TT
Tyre size	10.00-20
LI/SS	145;B

## Dimensions IS Standard

SW (IS) (mm)	277
OD (IS) (mm)	1080
SLR (IS) (mm)	500
RC (IS) (mm)	3336
Rim Rec	7.5
Rim Alt	7.0; 8.0
TRA Code	E2

## Load Capacity (IS)

km/h / bar	6.50
50	2900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..