



AW 708

Description

AW 708 has been developed for soil tillage, transport and hay harvesting applications with implement machinery, trailers and balers. An HD version is available with a special cut-and-chip resistant compound.

UM

US Standard

Construction

◆ Bias

Machinery

Agriculture ▪ Baler, Industrial & Construction ▪ Trailer



Version	SPECIAL
Tire Type	TT
Tyre size	400/60-15.5
LI/SS	

Dimensions US Standard

USA Code	94051250
SW (US) (in)	15.9
OD (US) (in)	34.4
SLR (US) (in)	15.0
RC (US) (in)	100.9
Rim Rec	AG 13.00
ECE	E11-106R-004255

Load Capacity (US)

mph / psi	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..