



RIDEMAX FL 615



Description

RIDEMAX FL 615 is a radial flotation tire suitable for non-driven wheels of trailers, tankers and spreaders. The steel-belted structure offers high puncture resistance along with increased durability and high load capacity. RIDEMAX FL 615 provides low rolling resistance on the road with outstanding self-cleaning properties in the fields. The rounded shoulder and wide footprint area ensure best soil protection.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Trailer

Version	STEEL BELTED
Tire Type	TL
Tyre size	800/65R32
LI/SS	190;D

Dimensions IS Standard

SW (IS) (mm)	815
OD (IS) (mm)	1850
SLR (IS) (mm)	811
RC (IS) (mm)	5610
Rim Rec	DW 28 B
Rim Alt	DW 27 B
ECE	E11-106R-0010408

Load Capacity (IS)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8
65	5195	5830	7105	8060	9330	10600
50	6080	6825	8315	9430	10920	12405
40	6705	7525	9165	10395	12035	13675
30	7330	8225	10020	11365	13160	14950
25	7590	8515	10375	11765	13625	15480
20	7900	8865	10800	12250	14185	16115
10	8520	9565	11650	13215	15300	17385

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..