



US standard



GROWING TOGETHER

# MULTI RIB



PRODUCT DATA SHEET



Bias



# MULTI RIB

MULTI RIB is an agro-industrial tire for soil tillage and transport applications with 2WD tractors and implement machinery. It offers excellent handling throughout its long product life-cycle. Several versions are available for every need: an "aramid belted" version with improved puncture resistance, while the "HD" is made of a special cut-and-chip resistance compound.

### Technologies



Aramid Belted



Heavy Duty

### Performance



Cut and Chip Resistance



Durability



High Puncture Resistance



Steering Control

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 16"	94052516	11.00 - 16	W 10 L	W 8; W 8 L	12.4	36.6	-	-	15	70	AB HD	12	TL	-
	94061624	11.00 - 16	W 10 L	W 8; W 8 L	12.4	36.6	-	-	15	74	HD	12	TL	-
	94006199	11.00 - 16	W 10 L	W 8; W 8 L	12.4	36.6	-	-	15	67	STD	12	TL	-

AB HD: Aramid Belted Heavy Duty - HD: Heavy Duty - STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference