



US standard



GROWING TOGETHER

# XL GRIP (SCRAPER)



PRODUCT DATA SHEET



Bias

E-3



# XL GRIP (SCRAPER)



XL GRIP (SCRAPER) is a non-directional wide-base tire, particularly suitable for scrapers on any terrain. The tire features a strong casing and a special tread compound providing high cut and puncture resistance as well as excellent durability and traction even during heavy-duty operations. Additional features are best self-cleaning properties and exceptional stability.

## Performance



Cut Resistance



Durability



Heavy Duty



Self-Cleaning



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 29"	94063604	29.5 - 29	TL	28	-	STD	E-3	-	77.4	29.9	-	-	49	1200	25.00/3.5	26.00/3.5
	94055487	33.25 - 29	TL	32	-	STD	E-3	-	83.5	33.9	-	-	58	1566	27.00/3.5	26.00/3.5
Ø 35"	94057429	33.25 - 35	TL	32	-	STD	E-3	-	89.4	33.9	-	-	58	1703	27.00/3.5	29.00/3.5
	94062355	33.25 - 35	TL	38	-	STD	E-3	-	89.4	33.9	-	-	58	1808	27.00/3.5	29.00/3.5
	94058556	37.25 - 35	TL	36	-	STD	E-3	-	93.1	37.6	-	-	66	2160	31.00/4.0	29.00/3.5
Ø 39"	94059263	37.5 - 39	TL	52	-	STD	E-3	-	101.2	38.4	-	-	66	2622	32.00/4.5	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference